



Remote Sensing System

EM27

Environmental Monitoring

Innovation with Integrity

The EM 27 is an FT-IR Remote Sensing System. Providing highest performance, the EM 27 can easily be deployed in the field for various applications. Contamination of air, emissions from smoke stacks, diffuse emissions from waste disposals or hazardous emissions from chemical accidents can be observed with an operating range of up to several kilometers. The ethernet enabled system displays analysis results in real time. With optional detectors, beamsplitters the capabilities of the system can be adapted to the application.

Features

- Remote sensing of hazardous gases
- Remote sensing of aircraft emissions
- Control of diffuse emissions of waste disposals
- Fence-line monitoring at chemical factories and stocks
- Surveillance of waste disposal facilities
- Observation of stack gas plumes
- Ambient air monitoring

Key Features

- Several detector options available
- Telescopic sight available
- Highest performance in the field
- Real-time analysis
- Ethernet connectivity to analysis PC
- Operation from battery pack (option)

Sensor module

Type	Michelson type RockSolid™ interferometer
Size	400 mm x 360 mm x 270 mm
Weight	18 kg
Power Supply	110 V-240 VAC input voltage, 24 V battery pack (option)
Power consumption	40 W (average), 80 W (maximum)
Data interface	Ethernet

Optics

Field of View (FOV)	30 mrad (1.7 °), with 3:1 telescope: 10 mrad (0.57°)
Optical throughput	0.0082 sr cm ²
f-number	0.9
Entrance window	ZnSe
Beam splitter	KBr or ZnSe (option)
Detector	Liquid nitrogen cooled MCT detector, closed cycle cryo-cooled MCT detector (option)
Spectral resolution	$\Delta\sigma = 1 \text{ cm}^{-1}$ (0.5 cm ⁻¹ optional)
Wavenumber accuracy	<0,05 cm ⁻¹

Scan speed

at $\Delta\sigma = 4 \text{ cm}^{-1}$	4.6 spectra per second (two-sided interferograms) 9 spectra per second with split of interferograms
with ultrafast scanning option	16 spectra per second (two-sided interferograms) 32 spectra per second with split of interferograms
at $\Delta\sigma = 0.5 \text{ cm}^{-1}$	0.5 spectra per second 1.3 spectra per second with split of interferograms
with ultrafast scanning option	2.6 spectra per second 5 spectra per second with split of interferograms
NETD* for a single spectrum	0.02 K at Tb = 30 °C and $\sigma = 1,000 \text{ cm}^{-1}$
NESR* for a single spectrum	0.033 mW / (m ² sr cm ⁻¹) at Tb = 30 °C and $\sigma = 1,000 \text{ cm}^{-1}$
Spectral range	$\sigma = 700 - 5000 \text{ cm}^{-1}$ (active mode) $\sigma = 700 - 3800 \text{ cm}^{-1}$ (active mode with ultrafast scanning) $\sigma = 700 - 2200 \text{ cm}^{-1}$ (passive mode)
Internal black body (BB)	Peltier cooled BB: temperature range from dew point up to 80 °C (accuracy +/- 1 K), stabilized

(*) NETD: Noise Equivalent Temperature Difference

NESR: Noise Equivalent Radiance calculated from a double sided forward backward interferogram at $dv = 4 \text{ cm}^{-1}$, narrow band MCT detector

Bruker Optics is continually improving its products and reserves the right to change specifications without notice.
© 2022 Bruker Optics BOPT01

Bruker Optics GmbH & Co. KG
info.bopt.de@bruker.com

bruker.com

**Bruker Optics is ISO 9001, ISO 13485,
ISO 14001 and ISO 50001 certified.**

Online information
www.bruker.com/
EM27

Remote Sensing
www.bruker.com/
remotesensing

